

Genetron® 407A**000000013646**

Version 1.4

Revision Date 10/10/2024

Print Date 10/21/2024

SECTION 1. IDENTIFICATION

Product name : Genetron® 407A

Number : 000000013646

Product Use Description : Refrigerant

Manufacturer or supplier's details : Honeywell International Inc.
115 Tabor Road
Morris Plains, NJ 07950-2546

For more information call : 800-522-8001
+1-973-455-6300(Monday-Friday, 9:00am-5:00pm)

In case of emergency call : Medical: 1-800-498-5701 or +1-303-389-1414
: Transportation (CHEMTREC): 1-800-424-9300 or
+1-703-527-3887
:
: (24 hours/day, 7 days/week)

SECTION 2. HAZARDS IDENTIFICATION**Emergency Overview**

Form : Liquefied gas

Color : colourless

Odor : slight

Classification of the substance or mixture

Classification of the substance or mixture : Gases under pressure, Liquefied gas
Simple Asphyxiant

GHS Label elements, including precautionary statements

Genetron® 407A**000000013646**

Version 1.4

Revision Date 10/10/2024

Print Date 10/21/2024

Symbol(s)

:



Signal word

: Warning

Hazard statements

: Contains gas under pressure; may explode if heated.
May displace oxygen and cause rapid suffocation.

Precautionary statements

: **Prevention:**
Use personal protective equipment as required.**Storage:**

Protect from sunlight. Store in a well-ventilated place.

Hazards not otherwise
classified: Excessive exposure may cause central nervous system effects
including drowsiness and dizziness. Excessive exposure may
also cause cardiac arrhythmia.
May cause frostbite.**Carcinogenicity**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature

: Mixture

Chemical name	CAS-No.	Concentration
1,1,1,2-Tetrafluoroethane	811-97-2	40.00 %
Pentafluoroethane	354-33-6	40.00 %
Difluoromethane	75-10-5	20.00 %

Genetron® 407A**000000013646**

Version 1.4

Revision Date 10/10/2024

Print Date 10/21/2024

SECTION 4. FIRST AID MEASURES

- General advice : First aider needs to protect himself. Move out of dangerous area. Take off all contaminated clothing immediately.
- Inhalation : Move to fresh air. If breathing is irregular or stopped, administer artificial respiration. Use oxygen as required, provided a qualified operator is present. Call a physician. Do not give drugs from adrenaline-ephedrine group.
- Skin contact : After contact with skin, wash immediately with plenty of water. If there is evidence of frostbite, bathe (do not rub) with lukewarm (not hot) water. If water is not available, cover with a clean, soft cloth or similar covering. If symptoms persist, call a physician.
- Eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In case of frostbite water should be lukewarm, not hot. If symptoms persist, call a physician.
- Ingestion : Unlikely route of exposure. As this product is a gas, refer to the inhalation section. Do not induce vomiting without medical advice. Call a physician immediately.

Notes to physician

- Indication of immediate medical attention and special treatment needed, if necessary : Because of the possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used with special caution and only in situations of emergency life support. Treatment of overexposure should be directed at the control of symptoms and the clinical conditions. Treat frost-bitten areas as needed.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : The product is not flammable.
ASHRAE 34
Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
- Specific hazards during firefighting : Contents under pressure.
This product is not flammable at ambient temperatures and

Genetron® 407A**000000013646**

Version 1.4

Revision Date 10/10/2024

Print Date 10/21/2024

atmospheric pressure.
However, this material can ignite when mixed with air under pressure and exposed to strong ignition sources.
Container may rupture on heating.
Cool closed containers exposed to fire with water spray.
Do not allow run-off from fire fighting to enter drains or water courses.
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
Fire may cause evolution of:
Hydrogen fluoride
Carbon oxides
Halogenated compounds
Carbonyl halides

Special protective equipment for firefighters : In the event of fire and/or explosion do not breathe fumes.
Wear self-contained breathing apparatus and protective suit.
No unprotected exposed skin areas.

Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Immediately evacuate personnel to safe areas.
Keep people away from and upwind of spill/leak.
Wear personal protective equipment. Unprotected persons must be kept away.
Remove all sources of ignition.
Avoid skin contact with leaking liquid (danger of frostbite).
Ventilate the area.
After release, disperses into the air.
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
Avoid accumulation of vapours in low areas.
Unprotected personnel should not return until air has been tested and determined safe.
Ensure that the oxygen content is $\geq 19.5\%$.

Environmental precautions : Prevent further leakage or spillage if safe to do so.
The product evaporates readily.

Genetron® 407A**000000013646**

Version 1.4

Revision Date 10/10/2024

Print Date 10/21/2024

Methods and materials for
containment and cleaning
up : Ventilate the area.

SECTION 7. HANDLING AND STORAGE**Handling**

Precautions for safe
handling : Handle with care.
Avoid inhalation of vapour or mist.
Do not get on skin or clothing.
Wear personal protective equipment.
Pressurized container. Protect from sunlight and do not expose
to temperatures exceeding 50 °C.
Follow all standard safety precautions for handling and use of
compressed gas cylinders.
Use authorized cylinders only.
Protect cylinders from physical damage.
Do not puncture or drop cylinders, or expose them to open flame
or excessive heat.
Do not pierce or burn, even after use. Do not spray on a naked
flame or any incandescent material.
Do not remove screw cap until immediately ready for use.
Always replace cap after use.

Advice on protection against
fire and explosion : The product is not flammable.
Can form a combustible mixture with air at pressures above
atmospheric pressure.

Storage

Conditions for safe storage,
including any
incompatibilities : Pressurized container: protect from sunlight and do not expose
to temperatures exceeding 50 °C. Do not pierce or burn, even
after use.
Keep containers tightly closed in a dry, cool and well-ventilated
place.
Storage rooms must be properly ventilated.
Ensure adequate ventilation, especially in confined areas.
Protect cylinders from physical damage.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Genetron® 407A**000000013646**

Version 1.4

Revision Date 10/10/2024

Print Date 10/21/2024

- Protective measures : Do not breathe vapor.
Do not get in eyes, on skin, or on clothing.
Ensure that eyewash stations and safety showers are close to the workstation location.
- Engineering measures : General room ventilation is adequate for storage and handling.
Perform filling operations only at stations with exhaust ventilation facilities.
- Eye protection : Wear as appropriate:
Safety glasses with side-shields
If splashes are likely to occur, wear:
Goggles or face shield, giving complete protection to eyes
- Hand protection : Leather gloves
In case of contact through splashing:
Protective gloves
Neoprene gloves
Polyvinyl alcohol or nitrile- butyl-rubber gloves
- Skin and body protection : Avoid skin contact with leaking liquid (danger of frostbite).
Wear cold insulating gloves/ face shield/ eye protection.
- Respiratory protection : In case of insufficient ventilation wear suitable respiratory equipment.
Wear a positive-pressure supplied-air respirator.
Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
For rescue and maintenance work in storage tanks use self-contained breathing apparatus.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
Ensure adequate ventilation, especially in confined areas.
Do not get in eyes, on skin, or on clothing.
Remove and wash contaminated clothing before re-use.
Keep working clothes separately.

Exposure Guidelines

Components	CAS-No.	Value	Control parameters	Update	Basis

SAFETY DATA SHEET

Honeywell**Genetron® 407A****000000013646**

Version 1.4

Revision Date 10/10/2024

Print Date 10/21/2024

1,1,1,2-Tetrafluoroethane	811-97-2	TWA : Time weighted average	(1,000 ppm)		Honeywell:Limit established by Honeywell International Inc.
1,1,1,2-Tetrafluoroethane	811-97-2	TWA : Time weighted average	4,240 mg/m3 (1,000 ppm)	2020	WEEL:US Workplace Environmental Exposure Level
Pentafluoroethane	354-33-6	TWA : Time weighted average	(1,000 ppm)		Honeywell:Limit established by Honeywell International Inc.
Pentafluoroethane	354-33-6	TWA : Time weighted average	4,900 mg/m3 (1,000 ppm)	2020	WEEL:US Workplace Environmental Exposure Level
Difluoromethane	75-10-5	TWA : Time weighted average	2,200 mg/m3 (1,000 ppm)	2007	WEEL:US Workplace Environmental Exposure Level
Difluoromethane	75-10-5	TWA : Time weighted average	(1,000 ppm)	1994	Honeywell:Limit established by Honeywell International Inc.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : Liquefied gas
 Color : colourless
 Odor : slight

Genetron® 407A**000000013646**

Version 1.4

Revision Date 10/10/2024

Print Date 10/21/2024

Melting point/ range	:	Note: No data available
Boiling point/boiling range	:	-45 °C
Flash point	:	Note: Not applicable
Lower explosion limit	:	Note: None
Upper explosion limit	:	Note: None
Vapor pressure	:	11,270 hPa at 21.1 °C(70.0 °F) 25,667 hPa at 54.4 °C(129.9 °F)
Vapor density	:	3.1
Density	:	1.145 g/cm ³ at 25 °C
Partition coefficient: n-octanol/water	:	log Pow: 1.06 Note: 1,1,1,2-tetrafluoroethane (HFC-134a) log Pow: 1.48 Note: Ethane, pentafluoro- (HFC-125)
Decomposition temperature	:	> 250 °C

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Genetron® 407A**000000013646**

Version 1.4

Revision Date 10/10/2024

Print Date 10/21/2024

Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Hazardous polymerisation does not occur.
Conditions to avoid	: Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Decomposes under high temperature. Some risk may be expected of corrosive and toxic decomposition products. Can form a combustible mixture with air at pressures above atmospheric pressure. Do not mix with oxygen or air above atmospheric pressure.
Incompatible materials	: Potassium Calcium Powdered metals Finely divided aluminium Finely divided magnesium Zinc
Hazardous decomposition products	: Halogenated compounds Hydrogen fluoride Carbonyl halides Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Acute inhalation toxicity 1,1,1,2-Tetrafluoroethane	: LC50: > 500000 ppm, gas Exposure time: 4 h Species: Rat
Pentafluoroethane	: > 769000 ppm Exposure time: 4 h Species: Rat
Difluoromethane	: LC50: > 520000 ppm Exposure time: 4 h

Genetron® 407A**000000013646**

Version 1.4

Revision Date 10/10/2024

Print Date 10/21/2024

Species: Rat

Sensitisation

1,1,1,2-Tetrafluoroethane : Cardiac sensitization
Species: dogs
Note: No-observed-effect level
50 000 ppm
Lowest observed effect level
75 000 ppm

Pentafluoroethane : Cardiac sensitization
Species: dogs
Note: No-observed-effect level
75 000 ppm
Lowest observed effect level
100 000 ppm

Difluoromethane : Cardiac sensitization
Species: dogs
Note: No-observed-effect level
>350 000 ppm

Repeated dose toxicity

1,1,1,2-Tetrafluoroethane : Species: Rat
NOEL: 40000 ppm

Pentafluoroethane : Species: Rat
Application Route: Inhalation
Exposure time: (4 Weeks)
NOEL: 50000 ppm
Subchronic toxicity

Difluoromethane : Species: Rat
Application Route: Inhalation
Exposure time: (90 d)
NOEL: 50000 ppm
Subchronic toxicity

Genotoxicity in vitro

1,1,1,2-Tetrafluoroethane : Note: In vitro tests did not show mutagenic effects

Pentafluoroethane : Test Method: Ames test
Result: negative

Genetron® 407A**000000013646**

Version 1.4

Revision Date 10/10/2024

Print Date 10/21/2024

- Difluoromethane : Test Method: Ames test
Result: negative
- : Cell type: Human lymphocytes
Result: negative
- : Cell type: Chinese Hamster Ovary Cells
Result: negative
- : Cell type: Human lymphocytes
Result: negative
Method: Mutagenicity (in vitro mammalian cytogenetic test)
- : Test Method: Chromosome aberration test in vitro
Result: negative
- Genotoxicity in vivo
Difluoromethane : Species: Mouse
Cell type: Bone marrow
Method: Mutagenicity (micronucleus test)
Result: negative
- Teratogenicity
Pentafluoroethane : Species: Rabbit
Application Route: Inhalation exposure
NOAEL, Teratog: 50,000 ppm
NOAEL, Maternal: 50,000 ppm
Note: Did not show teratogenic effects in animal experiments.
- Species: Rat
Application Route: Inhalation exposure
NOAEL, Teratog: 50,000 ppm
NOAEL, Maternal: 50,000 ppm
Note: Did not show teratogenic effects in animal experiments.
- Difluoromethane : Species: Rat
Dose: NOEL - 50,000 ppm
Note: Did not show teratogenic effects in animal experiments.
- Species: Rabbit
Dose: NOEL - 50,000 ppm

Genetron® 407A**000000013646**

Version 1.4

Revision Date 10/10/2024

Print Date 10/21/2024

Note: Did not show teratogenic effects in animal experiments.

Further information

1,1,1,2-Tetrafluoroethane

: Note:

Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.

Rapid evaporation of the liquid may cause frostbite.

Avoid skin contact with leaking liquid (danger of frostbite).

SECTION 12. ECOLOGICAL INFORMATION

Biodegradability

Pentafluoroethane

: Result: Not readily biodegradable.

Value: 5 %

Method: OECD 301 D

Difluoromethane

: Note: Minimal

Further information on ecology

Additional ecological information

: This product is subject to U.S. Environmental Protection Agency Clean Air Act Regulations at 40 CFR Part 82. This product contains greenhouse gases which may contribute to global warming. Do NOT vent to the atmosphere. To comply with provisions of the U.S. Clean Air Act, any residual must be recovered.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

: Observe all Federal, State, and Local Environmental regulations.

Note

: This product is subject to U.S. Environmental Protection Agency Clean Air Act Regulations Section 608 in 40 CFR Part 82 regarding refrigerant recycling.

SECTION 14. TRANSPORT INFORMATION

Genetron® 407A**000000013646**

Version 1.4

Revision Date 10/10/2024

Print Date 10/21/2024

DOT	UN/ID No.	: UN 3338
	Proper shipping name	: REFRIGERANT GAS R 407A
	Class	: 2.2
	Packing group	
	Hazard Labels	: 2.2
IATA	UN/ID No.	: UN 3338
	Description of the goods	: REFRIGERANT GAS R 407A
	Class	: 2.2
	Hazard Labels	: 2.2
	Packing instruction (cargo aircraft)	: 200
	Packing instruction (passenger aircraft)	: 200
IMDG	UN/ID No.	: UN 3338
	Description of the goods	: REFRIGERANT GAS R 407A
	Class	: 2.2
	Hazard Labels	: 2.2
	EmS Number	: F-C, S-V
	Marine pollutant	: no
	IMDG Code segregation group according chapter 3.1.4.4	: NONE,

SECTION 15. REGULATORY INFORMATION**Inventories**

USA. List of Active Substances on the Toxic Substances Control Act (TSCA) Chemical Substances Inventory, as amended : On TSCA Inventory

Australia. Inventory of Industrial Chemicals (AIC), as amended : On the inventory, or in compliance with the inventory

Canada. Domestic Substances List (DSL), as amended : All components of this product are on the Canadian DSL

Genetron® 407A**000000013646**

Version 1.4

Revision Date 10/10/2024

Print Date 10/21/2024

Japan. Kashin-Hou Law List : On the inventory, or in compliance with the inventory

Korea. Existing Chemicals Inventory (KECI) : On the inventory, or in compliance with the inventory

Philippines. Inventory of Chemicals and Chemical Substances (PICCS) : On the inventory, or in compliance with the inventory

China. Inventory of Existing Chemical Substances (IECSC) : On the inventory, or in compliance with the inventory

New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand : On the inventory, or in compliance with the inventory

Taiwan Chemical Substance Inventory (TCSI) : Not in compliance with the inventory

National regulatory information

SARA 302 Components : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards : Acute Health Hazard
Sudden Release of Pressure Hazard

California Prop. 65 :



WARNING: This product can expose you to chemicals, listed below, known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Chloromethane

74-87-3

Genetron® 407A**000000013646**

Version 1.4

Revision Date 10/10/2024

Print Date 10/21/2024

New Jersey RTK	: 1,1,1,2-Tetrafluoroethane	811-97-2
	: Pentafluoroethane	354-33-6
	: Difluoromethane	75-10-5
Pennsylvania RTK	: 1,1,1,2-Tetrafluoroethane	811-97-2
	: Pentafluoroethane	354-33-6
	: Difluoromethane	75-10-5

SECTION 16. OTHER INFORMATION

	HMIS III	NFPA
Health hazard	: 1	2
Flammability	: 1	1
Physical Hazard	: 0	
Instability	:	0

Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user. This information should not constitute a guarantee for any specific product properties.

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Previous Issue Date: 10/31/2019

Prepared by Honeywell Energy and Sustainability Solutions Product Stewardship Group Product Stewardship Group