

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Honeywell

Solstice® 454A

000000026521

Version 1.1

Revision Date 09.01.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : Solstice® 454A
SDS-number : 000000026521
Type of product : Mixture
Remarks : SDS according to Art. 31 of Regulation (EC) 1907/2006.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Refrigerant
Uses advised against : Consumer use

1.3. Details of the supplier of the safety data sheet

Company : Honeywell Advanced Limited Honeywell International, Inc.
One Spencer Dock, North Wall 115 Tabor Road
Quay Morris Plains, NJ 07950-2546
Dublin 1 USA
Ireland
Telephone : +353 1 447 9350
For further information, please contact: : SafetyDataSheet@Honeywell.com

1.4. Emergency telephone number

Emergency telephone number : +1-703-527-3887 (ChemTrec-Transport)
+1-303-389-1414 (Medical)
: Poison Control Center:
United Kingdom: (+44) 844 892 0111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

REGULATION (EC) No 1272/2008

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Honeywell

Solstice® 454A

000000026521


Version 1.1

Revision Date 09.01.2025

Flammable gases Category 1B
H221 Flammable gas.
Gases under pressure Liquefied gas
H280 Contains gas under pressure; may explode if heated.

2.2. Label elements

REGULATION (EC) No 1272/2008

Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	H221 Flammable gas. H280 Contains gas under pressure; may explode if heated.
Precautionary statements	:	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely. P381 In case of leakage, eliminate all ignition sources. P410 + P403 Protect from sunlight. Store in a well-ventilated place.
Special labelling of certain products:	:	Contains fluorinated greenhouse gases.

2.3. Other hazards

Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Rapid evaporation of the liquid may cause frostbite. This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher. The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Honeywell

Solstice® 454A

000000026521

Version 1.1

Revision Date 09.01.2025

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Chemical name	CAS-No. Index-No. REACH Registration Number EC-No.	Classification 1272/2008	Concentration	Remarks
2,3,3,3-Tetrafluoroprop-1-ene	754-12-1 468-710-7	Press. Gas Liquefied gas; H280 Flam. Gas 1B; H221	65 %	
Difluoromethane	75-10-5 200-839-4	Flam. Gas 1B; H221 Press. Gas ; H280	35 %	

Remaining components of this product are non-hazardous and/or are present at concentrations below reportable limits.

Occupational Exposure Limit(s), if available, are listed in Section 8.

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice:

First aider needs to protect himself. Move out of dangerous area. Take off all contaminated clothing immediately.

Inhalation:

When inhaled remove to fresh air and seek medical aid. If breathing is irregular or stopped, administer artificial respiration. If unconscious, place in recovery position and seek medical advice.

Skin contact:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Honeywell

Solstice® 454A

000000026521

Version 1.1

Revision Date 09.01.2025

Rapid evaporation of the liquid may cause frostbite. In case of contact with liquid, thaw frosted parts with water, then remove clothing carefully. Wash with plenty of water. Wash contaminated clothing before re-use. Consult a physician.

Eye contact:

Protect unharmed eye. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Call a physician immediately.

Ingestion:

Ingestion is unlikely because of the physical properties and is not expected to be hazardous.

4.2. Most important symptoms and effects, both acute and delayed

No data available

4.3. Indication of any immediate medical attention and special treatment needed

Adrenaline derivatives are contra-indicated. Treat symptomatically.

See Section 11 for more detailed information on health effects and symptoms.

:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Honeywell

Solstice® 454A

000000026521

Version 1.1

Revision Date 09.01.2025

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Flammable gas.

Contents under pressure.

Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.

Vapors may travel to areas away from work site before igniting/flashing back to vapor source.

Fire or intense heat may cause violent rupture of packages.

Cool closed containers exposed to fire with water spray.

Do not allow run-off from fire fighting to enter drains or water courses.

In case of fire hazardous decomposition products may be produced such as:

Hydrogen fluoride

Carbonyl halides

Carbon monoxide

Carbon dioxide (CO₂)

5.3. Advice for firefighters

Wear full protective clothing and self-contained breathing apparatus.

Evacuate personnel to safe areas. Leaking gas fire: Do not extinguish, unless leak can be stopped safely. Eliminate all ignition sources if safe to do so.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Immediately evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Wear personal protective equipment. Unprotected persons must be kept away. Wear self-contained breathing apparatus and protective suit. Eliminate all ignition sources if safe to do so. Avoid skin contact with leaking liquid (danger of frostbite). Ventilate the area. Vapors may travel to areas away from work site before igniting/flashing back to vapor source. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing. Ensure that the oxygen content is $\geq 19.5\%$.

6.2. Environmental precautions

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Honeywell

Solstice® 454A

000000026521

Version 1.1

Revision Date 09.01.2025

The product evaporates readily. Prevent product from entering drains.

6.3. Methods and materials for containment and cleaning up

Use explosion-proof equipment.

No sparking tools should be used.

Ventilate the area.

Allow to evaporate.

Inform the responsible authorities in case of gas leakage, or of entry into waterways, soil or drains.

Pay attention to the spreading of gases especially at ground level (heavier than air) and to the direction of the wind.

6.4. Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling:

Exhaust ventilation at the object is necessary. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Use suitably rated equipment.

Advice on protection against fire and explosion:

Keep product and empty container away from heat and sources of ignition. Fire or intense heat may cause violent rupture of packages. Use suitably rated equipment.

Hygiene measures:

Provide adequate ventilation. Do not smoke. When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities

Further information on storage conditions:

Keep containers tightly closed in a cool, well-ventilated place. Containers should be protected against falling down. Protect from warmth. Keep away from direct sunlight. Keep only in the original container at temperature not exceeding 50°C

7.3. Specific end use(s)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Honeywell

Solstice® 454A

000000026521

Version 1.1

Revision Date 09.01.2025

no additional data available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits:

Components	Basis / Value type	Value / Form of exposure	Exceeding Factor	Remarks
2,3,3,3-Tetrafluoroprop-1-ene	WEEL TWA	500 ppm		
2,3,3,3-Tetrafluoroprop-1-ene	HONEYWELL TWA	500 ppm		
Difluoromethane	HONEYWELL TWA	2.200 mg/m3 1.000 ppm		We are not aware of any national exposure limit.

WEEL - US Workplace Environmental Exposure Level

TWA - Time weighted average

DNEL/ PNEC-Values

Component	End-use/impact	Exposure duration	Value	Exposure routes	Remarks
2,3,3,3-Tetrafluoroprop-1-ene	Workers / Long-term systemic effects		950 mg/m3	Inhalation	
2,3,3,3-Tetrafluoroprop-1-ene	Consumers / Long-term systemic effects		113,1 mg/m3	Inhalation	
2,3,3,3-Tetrafluoroprop-1-ene	Workers / Acute systemic effects		186400 mg/m3	Inhalation	
2,3,3,3-Tetrafluoroprop-1-ene	Consumers / Acute systemic effects		186400 mg/m3	Inhalation	
Difluoromethane	Workers /		7035	Inhalation	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Honeywell

Solstice® 454A

000000026521

Version 1.1

Revision Date 09.01.2025

	Long-term systemic effects		mg/m ³		
Difluoromethane	Consumers / Long-term systemic effects		750 mg/m ³	Inhalation	

Component	Environmental compartment / Value	Remarks
2,3,3,3-Tetrafluoroprop-1-ene	Fresh water: 0,1 mg/l	
2,3,3,3-Tetrafluoroprop-1-ene	Marine water: 0,01 mg/l	
2,3,3,3-Tetrafluoroprop-1-ene	Fresh water sediment: 1,51 mg/kg	
2,3,3,3-Tetrafluoroprop-1-ene	Marine sediment: 0,151 mg/kg	
2,3,3,3-Tetrafluoroprop-1-ene	Soil: 1,49 mg/kg	
Difluoromethane	Fresh water: 0,142 mg/l	Assessment factor: 1000
Difluoromethane	Fresh water sediment: 0,534 mg/kg dw	

8.2. Exposure controls

Occupational exposure controls

The Personal Protective Equipment must be in accordance with EN standards:respirator EN 136, 140, 149; safety glasses EN 166; protective suit: EN 340, 463, 468, 943-1, 943-2; gloves EN 374, 511; safety shoes EN-ISO 20345.

Engineering measures

Highly effective exhaust ventilation

Personal protective equipment

Respiratory protection:

In case of insufficient ventilation wear suitable respiratory equipment.

Self-contained breathing apparatus (EN 133)

Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.

Hand protection:

Protective gloves against cold

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Honeywell

Solstice® 454A

000000026521

Version 1.1

Revision Date 09.01.2025

(EN 511)

Eye protection:

Safety goggles

Skin and body protection:

Wear suitable protective equipment.

Environmental exposure controls

Handle in accordance with local environmental regulations and good industrial practices.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- | | | |
|-------------------------------------|---|----------------------------------|
| (a) Physical state | : | gaseous |
| (b) Colour | : | colourless |
| (c) Odour | : | slight, original odour |
| (d) Melting point/freezing point | : | No data available |
| (e) Boiling point/boiling range | : | No data available |
| (f) Flammability | : | Flammable gas. |
| (g) Lower and upper explosion limit | : | Lower explosion limit
8 %(V) |
| | : | Upper explosion limit
15 %(V) |
| (h) Flash point | : | Not applicable |
| (i) Auto-ignition temperature | : | No data available |
| (j) Decomposition temperature | : | Stable under normal conditions. |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Honeywell

Solstice® 454A

000000026521

Version 1.1

Revision Date 09.01.2025

- (k) pH : neutral
- (l) Viscosity, kinematic : No data available
- (m) Solubility(ies) : Water solubility:
No data available
- (n) Partition coefficient: n-
octanol/water : No data available
- (o) Vapour pressure : 1.041 kPa
at 21 °C
- (p) Density and / or relative
density : No data available
- (q) Relative vapour density : No data available
- (r) Particle characteristics : No data available

9.2 Other Information

- Oxidizing properties : The substance or mixture is not classified as oxidizing.
- Evaporation rate : No data available
- Viscosity, dynamic : No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Honeywell

Solstice® 454A

000000026521

Version 1.1

Revision Date 09.01.2025

Hazardous polymerisation does not occur.

10.4. Conditions to avoid

Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.
Heat, flames and sparks.
Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C.

10.5. Incompatible materials

Alkali metals
Oxidizers (e.g. peroxide residues present in insufficiently cured rubbers)
Finely divided metal powders such as aluminum, magnesium, or zinc.

10.6. Hazardous decomposition products

In case of fire hazardous decomposition products may be produced such as:
Hydrogen fluoride
Carbonyl halides
Carbon monoxide
Carbon dioxide (CO₂)

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

(a) *Acute toxicity*

Acute oral toxicity:
No data available

Acute dermal toxicity:
No data available

Acute inhalation toxicity:
No data available

Acute toxicity (other routes of administration):
No data available

(b) *Skin corrosion/irritation:*
No data available

(c) *Serious eye damage/eye irritation:*

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Honeywell

Solstice® 454A

000000026521

Version 1.1

Revision Date 09.01.2025

No data available

(d) Respiratory or skin sensitisation:

No data available

(h) STOT-single exposure:

No data available

(i) STOT - repeated exposure:

No data available

(j) Aspiration hazard:

No data available

11.2. Information on other hazards

Endocrine disrupting properties

No data available

Other information:

The product has not been tested. The information is derived from the properties of the individual components.

SECTION 12: Ecological information

12.1. Toxicity

Toxicity to fish:

No data available

Toxicity to aquatic plants:

No data available

Toxicity to aquatic invertebrates:

No data available

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Honeywell

Solstice® 454A

000000026521

Version 1.1

Revision Date 09.01.2025

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

No data available

12.6. Endocrine disrupting properties

No data available

12.7. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product:

Dispose according to legal requirements.

Packaging:

Legal requirements are to be considered in regard of reuse or disposal of used packaging materials

Further information:

Provisions relating to waste:

EC Directive 2006/12/EC; 2008/98/EEC

Regulation No. 1013/2006

For personal protection see section 8.

SECTION 14: Transport information

14.1 UN number or ID number

ADR/RID:3161

IMDG:3161

IATA:3161

14.2 UN proper shipping name

ADR/RID:LIQUEFIED GAS, FLAMMABLE, N.O.S.(DIFLUOROMETHANE, R-1234yf)

IMDG:LIQUEFIED GAS, FLAMMABLE, N.O.S.(DIFLUOROMETHANE, R-1234yf)

IATA:Liquefied gas, flammable, n.o.s.(Difluoromethane, R-1234yf)

14.3 Transport hazard class(es)

ADR/RID:2.1

IMDG: 2.1

IATA: 2.1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Honeywell

Solstice® 454A

000000026521

Version 1.1

Revision Date 09.01.2025

14.4 Packaging group

No data available

14.5 Environmental hazards

ADR/RID: no

Marine pollutant: no

14.6 Special precautions for user

IMDG Code segregation group according chapter 3.1.4.4 : NONE,

14.7 Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Basis	Value	Remarks
Directive 2012/18/EC SEVESO III Listed in Regulation : P2: Flammable gases	Quantity: 10 t Quantity: 50 t	
Substances of very high concern (SVHC)		This product does not contain substances of very high concern according to Regulation (EC) No Article 57 above the respective regulatory 1907/2006 (REACH), concentration limit of $\geq 0.1\%$ (w/w).
Regulation (EC) No. 1907/2006, Annex XIV		Not listed
Regulation (EC) No. 1907/2006, Annex XVII Number in Regulation: 40		Listed

Global warming potential :
237

Other inventory information

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Honeywell

Solstice® 454A

000000026521

Version 1.1

Revision Date 09.01.2025

USA. List of Active Substances on the Toxic Substances Control Act (TSCA) Chemical Substances Inventory, as amended

All substances listed as active on the TSCA inventory

Australian Inventory of Industrial Chemicals

All components are listed on the inventory, regulatory obligations/restrictions apply

Canada. Domestic Substances List (DSL), as amended

All components of this product are on the Canadian DSL

Japan. Kashin-Hou Law List

On the inventory, or in compliance with the inventory

Korea. Existing Chemicals Inventory (KECI)

On the inventory, or in compliance with the inventory

Philippines. Inventory of Chemicals and Chemical Substances (PICCS)

On the inventory, or in compliance with the inventory

China. Inventory of Existing Chemical Substances (IECSC)

On the inventory, or in compliance with the inventory

Thailand. Existing Chemicals Inventory from FDA (TECI List)

On the inventory, or in compliance with the inventory

Taiwan Chemical Substance Inventory (TCSI)

On the inventory, or in compliance with the inventory

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Text of H-statements referred to under heading 3

2,3,3,3-Tetrafluoroprop-1-ene : H280 Contains gas under pressure; may explode if heated.
H221 Flammable gas.

Difluoromethane : H221 Flammable gas.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended

Honeywell

Solstice® 454A

000000026521

Version 1.1

Revision Date 09.01.2025

H280 Contains gas under pressure; may explode if heated.

Further information

All directives and regulations refer to amended versions.

Vertical lines in the left hand margin indicate a relevant amendment from the previous version.

Abbreviations:

EC European Community

CAS Chemical Abstracts Service

DNEL Derived no effect level

PNEC Predicted no effect level

vPvB Very persistent and very bioaccumulative substance

PBT Persistent, bioaccumulative und toxic substance

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user.

This information should not constitute a guarantee for any specific product properties.
